

# Enerlites®

## DUPLEX SELF-GROUNDING TAMPER-RESISTANT RESIDENTIAL GRADE RECEPTACLE



MODEL NO: 62580-TR

### DESCRIPTION

ENERLITES residential grade receptacles are rated for variety of standard configuration. Each duplex is equipped with break-off plaster ears and tabs to allow for easy alignment and 2-circuit conversion. All duplex receptacles are designed with thermoplastic construction and feature a shallow build for maximum wiring room.

### FEATURES

- Optional grounding with self-grounding clip or green terminal screw
- Automatically ground to the metal outlet box
- Break-off tabs for easy two-circuit conversion
- Push-in #14 AWG Cu solid wire for 15A branch circuit only
- Shallow design for maximum wiring room
- Easy-access green hex head grounding screw
- Captive mounting screws
- Removable yoke tabs for ideal alignment
- Large head combination screws for fast wiring
- Terminal screws backed out ready for wiring
- Combination Slot/Phillips head mounting and terminal screws ease installation

### SPECIFICATIONS

Amperage	20 Amp
Voltage	125VAC
NEMA	5-20R
Termination	Rear Push In and Side
Material	Thermoplastic
Operating Temperature	-104° F to 167° F
Warranty	2 Years

### TESTING & CODE COMPLIANCE



### APPLICATIONS

- Homes
- Apartments
- Condominiums
- Offices
- Hotels
- Restaurants

### SPECIFICATION SUBMITTAL

Job Name

Job Number

Notes