



Documents



Replacement Part Catalog 1



Cut Sheets 2

Certificates

Certificate of suitability

UL

Electricity

Ampacity

125 A

Voltage / between phase and Ground (GND) / rated value

120 V

Voltage / between phase and phase /
rated value

240 V

General Technical Data

Configuration of the busbars

COPPER BUS

Phase number

1

Suitability for operation

RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION

Number of circuits / in a trunking unit

24

Mechanical Design

Design of the housing

TYPE 3R

Number of width units / for installation width

12

Model

product brand name

SIEMENS

Product type designation

PLUG-ON NEUTRAL READY PRO SERIES

Special product feature

GREY TRIM

Product sub brand name

LOAD CENTERS

Switching Capacity

Switching capacity current / acc. to EN 100000 A
60898 / rated value

100000 A

Product Selector Information

Product Type	Load Center
Main Type	Main Lug
Amp Rating	125
Phase	Single Phase (1PH - 3W)
Enclosure Type	Outdoor
Bus Material	CU
No. of 1 inch Spaces	12
No. of Circuits	24
Load Center Type	Load Center
Load Center Series	a) PN -1ph CU bus Plug-on Neut
Trim Color – Mounting Description	D) Gray - Surface Mount



Application and Selection Guide
3



Brochures 4



Application and Selection Guide
5



[Speed Fax Sections 6](#)



[Others 7](#)



[Drawing 8](#)