

Siemens GFCI circuit breakers are UL Listed and CSA Certified as Class A devices. These circuit breakers offer the new Self-Test and Lockout feature as required by UL 943, enabling the GFCI to automatically and continuously test itself to ensure that it is working properly. If it is detected that the device has been compromised, the device trips itself and locks out the homeowner from resetting the device, reducing the possibility of the homeowner incorrectly assuming that the device was tripped to prevent a ground fault.



- 10kA interrupting rating
- Includes self-test as required by UL 943 as an added safety feature
- Single pole, 120-Volt, 20 Amp GFCI circuit breaker
- Suitable for a variety of construction applications including spas, hot tubs, kitchens, bathrooms, etc.

Documents



Information and Instruction 1



Speed Fax Sections 2

Certificates

Standard	UL / CSA
----------	----------

Electricity

Voltage / between phase and Ground (GND) / rated value	120 V
Supply voltage frequency / rated value / 50/60 Hz	1
Continuous current / rated value	20 A

General Technical Data

Suitability for operation	PERSONEL PROTECTION
Number of poles	1

Mechanical Design

Design of the product	QPF2
Design of the overload release	THERMAL-MAGNETIC

Model

Type of electrical connection	PLUG-IN
Product brand name	SIEMENS
Type of connectable conductor cross-sections / at AWG conductors	14 - 10AWG (CU) / 12 - 8AWG (AL)
Product feature	10kA INTERRUPT
Type of mounting panel	LOADCENTER



Videos 3



Brochures 4



Brochures 5



Application and Selection Guide
6



Videos 7