



Documents



Speed Fax Sections 1



Cut Sheets 2

Certificates

Certificate of suitability UL

Electricity

Ampacity 100 A
Voltage / between phase and Ground (GND) / rated value 120 V
Voltage / between phase and phase / rated value 240 V

General Technical Data

Configuration of the busbars ALUMINUM BUS
Phase number 1
Suitability for operation RESIDENTIAL AND LIGHT
COMMERCIAL ELECTRIC
DISTRIBUTION
Number of circuits / in a trunking unit 32

Mechanical Design

Design of the housing TYPE 1
Size of the circuit-breaker 100A
Number of width units / for installation width 16

Model

product brand name SIEMENS
Product type designation PLUG-ON NEUTRAL READY
STANDARD SERIES
Special product feature GREY TRIM
Product sub brand name LOAD CENTERS

Switching Capacity

Switching capacity current / acc. to EN 60898 / rated value 22000 A

Product Selector Information

Product Type	Load Center
Main Type	Main Breaker
Amp Rating	100
Phase	Single Phase (1PH - 3W)
Enclosure Type	Indoor
Bus Material	AL
No. of 1 inch Spaces	16
No. of Circuits	32
Load Center Type	Load Center
Load Center Series	c) SN -1ph AL bus Plug-on Neut
Trim Color – Mounting Description	A) Gray - Standard Flush/Surface Combo



Brochures 3



Application and Selection Guide
4



Replacement Part Catalog 5



Application and Selection Guide
6



Drawing 7