



Documents



Cut Sheets 1



Application and Selection Guide

Certificates

Certificate of suitability UL

Electricity

Ampacity	200 A
Voltage / between phase and Ground (GND) / rated value	120 V
Voltage / between phase and phase / rated value	240 V

General Technical Data

Configuration of the busbars	ALUMINUM BUS
Phase number	1
Suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Number of circuits / in a trunking unit	16

Mechanical Design

Design of the housing	TYPE 3R
Size of the circuit-breaker	200A
Number of width units / for installation width	8

Model

product brand name	SIEMENS
Product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
Special product feature	GREY TRIM/ FEED THRU LUGS
Product sub brand name	LOAD CENTERS

Switching Capacity

Switching capacity current / acc. to EN 22000 A
60898 / rated value

Product Selector Information

Product Type	Load Center
Main Type	Main Breaker
Amp Rating	200
Phase	Single Phase (1PH - 3W)
Enclosure Type	Outdoor
Bus Material	AL
No. of 1 inch Spaces	8
No. of Circuits	16
Load Center Type	Load Center w/ Feed Thru Lug
Load Center Series	c) SN -1ph AL bus Plug-on Neut
Trim Color – Mounting Description	D) Gray - Surface Mount



[Drawing 3](#)



[Replacement Part Catalog 4](#)



[Brochures 5](#)



Others 6



Speed Fax Sections 7



Product Specification Guide 8



Application and Selection Guide
9