



## Documents



## Cut Sheets 1



## Others 2

## Certificates

Certificate of suitability UL

# Electricity

|                                                        |       |
|--------------------------------------------------------|-------|
| Ampacity                                               | 125 A |
| Voltage / between phase and Ground (GND) / rated value | 120 V |
| Voltage / between phase and phase / rated value        | 240 V |

## General Technical Data

|                                         |                                                              |
|-----------------------------------------|--------------------------------------------------------------|
| Configuration of the busbars            | ALUMINUM BUS                                                 |
| Phase number                            | 1                                                            |
| Suitability for operation               | RESIDENTIAL AND LIGHT<br>COMMERCIAL ELECTRIC<br>DISTRIBUTION |
| Number of circuits / in a trunking unit | 24                                                           |

## Mechanical Design

|                                                |         |
|------------------------------------------------|---------|
| Design of the housing                          | TYPE 3R |
| Number of width units / for installation width | 12      |

## Model

|                          |                                          |
|--------------------------|------------------------------------------|
| product brand name       | SIEMENS                                  |
| Product type designation | PLUG-ON NEUTRAL READY<br>STANDARD SERIES |
| Special product feature  | GREY TRIM                                |
| Product sub brand name   | LOAD CENTERS                             |

## Switching Capacity

Switching capacity current / acc. to EN 100000 A  
60898 / rated value

## Product Selector Information


|                                   |                                |
|-----------------------------------|--------------------------------|
| Product Type                      | Load Center                    |
| Main Type                         | Main Lug                       |
| Amp Rating                        | 125                            |
| Phase                             | Single Phase (1PH - 3W)        |
| Enclosure Type                    | Outdoor                        |
| Bus Material                      | AL                             |
| No. of 1 inch Spaces              | 12                             |
| No. of Circuits                   | 24                             |
| Load Center Type                  | Load Center                    |
| Load Center Series                | c) SN -1ph AL bus Plug-on Neut |
| Trim Color – Mounting Description | D) Gray - Surface Mount        |



Application and Selection Guide  
3



Speed Fax Sections 4




Replacement Part Catalog 5



Brochures 6



Application and Selection Guide  
7



Drawing 8